1023321311

# ZIPS-H | IP Horn Speaker

Zenitel IP Speaker - Horn

- Zenitel Audio Presence - crystal clear audio
- Protected from dust and Water - IP66
- Speaker-as-mic Technology
- External RJ45 connection
- Max. SPL: 120 dBA (1m)
- Ideal for Micro Zone PA and systems that require a limited number of speakers
- Each speaker is individually addressable and monitored
- ONVIF Compatible
- Remote software upgrade and configuration
- Relay output for remote control, e.g. doors, signal lamps, gates
- Powered from the IP network cable using Power over Ethernet (PoE)

SIP IC-Edge ICX-AlphaCom IP66 IK08 Audio Automatic Volume HD Voice

Network

## Description

The Zenitel IP Horn Speaker features a Class D amplifier, powered via PoE, and is designed with a horn shape to enhance both sound pressure level (SPL) and directivity. This design enables the speaker to deliver up to 120 dBA SPL peak signal (with a 6 dB crest factor), making it ideal for environments where speakers need to be positioned at a distance from the listener and where space is not a primary concern.

The ZIPS-H is at home in high-noise environments and where reflections must be controlled to maintain intelligibility such as ideal for road and tunnel infrastructure and industrial projects. Of course it is equally suited to building security applications where perimeter and asset protection may be the focus.

Leveraging IP technology, each speaker can be individually monitored and managed. With the amplifier integrated directly into the speaker, the need for a central amplifier unit and traditional speaker loops is eliminated, making the system highly scalable and simplifying the addition of new speakers.

While conventional speaker loops are not required, the speakers can still be grouped into zones that can extend across networks or even the Internet. To ensure maximum reliability, the speaker comes equipped with advanced supervision features.

The built-in microphone offers intelligent functionalities such as self-checking and automatic volume control. It also enhances traditional broadcast systems by enabling half-duplex communication and ambient listening. The self-checking feature detects any faults in the network or speaker electronics, with status updates sent to the central unit and third-party management systems via SNMP or Syslog. The speakers can



www.zenitel.com info@zenitel.com Last revision date: 2026-01-22 12:25

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

also be auto-discovered, receive messages, and provide talkback functionality directly through a VMS using ONVIF.

## Technical Dimensions








Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

## HORIZONTAL: 60°






www.zenitel.com info@zenitel.com Last revision date: 2026-01-22 12:25

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

## VERTICAL : 90°








Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

# Specifications

**GENERAL**

| | |
|---|---|
| Codecs | G.711, G.722 |
| Effective frequency range | 275 - 7000 Hz |
| Continuous SPL (6dB crest Factor) | 115 dBA |
| Max. SPL @ 1kHz/1m | 120 dBA |
| Output Power (Continuous/Peak) | 7.5W/30W |
| IP Rating | IP66 |
| Dimension (WxHxD) | 253 x 152 x 309 mm |
| Weight | 1,85 kg |
| Material, Color | ABS, grey |
| Mounting | Bracket, stainless steel grade 304 |
| Boxed Shipping weight | |
| Boxed Shipping dims (Width x Height x Depth) | |

**NETWORKING AND PROTOCOLS**

| | |
|---|---|
| Protocols | IPv4 (with DiffServ), SIP, TCP, UDP, HTTPS, TFTP, RTP, DHCP, SNMP, ONVIF, CCoIP® , NTP |
| LAN protocols | Power over Ethernet (IEEE 802.3 a-f) Network Access Control (IEEE 802.1x) |
| Management and operation | HTTP/HTTPS (Web configuration) DHCP and static IP + IC-EDGE. Remote automatic software upgrade. Centralized monitoring |
| Advanced supervision functions | E.g. network test, tone test, status reports |
| SIP support | RFC 3261 (SIP base standard), RFC 3515 (SIP refer), RFC 2976 (SIP info) |
| DTMF support | RFC 2833, 2976 (SIP info) |





Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

**HARDWARE**

| | |
|---|---|
| Ethernet connector | 1 x RJ 45 |
| All other connectors | Tool less, spring loaded, vibration proof terminals |
| General inputs and outputs | 1x GPIO; 1x mic/line input |
| Output | 12mA as LED drivers |
| Change-over relay (NO+COM) | 48V nominal, max. 100VDC, 70VAC |
| Power options | PoE |
| PoE (power over Ethernet) | IEEE 802.3af standard, Class 3 (6.49W to 12.95 W) |
| Max current consumption | 0.35 A |
| Secondary speaker line out | 8 Ohm |

**ENVIRONMENT AND COMPLIANCES**

| | |
|---|---|
| Operating temperature range | -40° to 70° C / -40° to 158 ° F |
| Storage temperature range | -40° to 70° C / -40° to 158 ° F |
| Relative humidity | < 95% not condensing |
| EMC | CE and FCC Part 15 |
| IP Rating | IP66 |
| IK Rating | IK08 |

**OTHER SPECIFICATIONS**

| | |
|---|---|
| System boot time | Under 10 seconds |
| IP address information | Speaker IP address on input short |
| Country of manufacture | Norway |
| Warranty | 2 Years standard warranty, extendible up to total of 5 years (additional fee) |

# Accessories



www.zenitel.com info@zenitel.com Last revision date: 2026-01-22 12:25

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

VLS-GLAND

Cable gland for VLS-15/30



www.zenitel.com info@zenitel.com Last revision date: 2026-01-22 12:25

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.